


Accuflex Beverage Transfer Products



Bevlex® 500 Series Tubing

Non-PVC tubing for draft beer transfer and soft drink applications. Translucent tubing is free from colorants and complies with applicable parts of FDA CFR Title 21 Parts 170 to 199 and NSF 51 Listed.

Construction: Special dual durometer TPE construction combines a clear low extraction inner contact surface with a flexible translucent outer layer, providing excellent kink resistance and taste protection properties.

Service Temperature: -40°F (-40°C) to +140°F (+60°C)

Features and Benefits:

- **PVC Free** — Contains no PVC, Phthalates or other chemicals listed in California Prop 65. Reduces plastics odor and taste.
- **Regulatory Compliance** — Meets FDA criteria, RoHS compliant, Reach SVHC compliant and is NSF 51 listed.
- **Chemical Compatibility** — Excellent chemical resistance and no taste carryover when Standard Caustic Solution (2-3%) is utilized in line cleaning at the recommended temperatures of 80°-110°F.
- **Fitting Retention** — Unlike competitive products fitting retention remains stable even after various temperature cycles.
- **Lighter Weight** — Up to 25% lighter weight than PVC.
- **Heavy Walled Construction** — To resist crushing and kinking, and provide ease of handling and routing.
- **Available Alternate Colors** — Red and Black colors are available on special order. Minimum quantities will apply.

Nominal Specifications

Part Number	Standard Package	Nominal		Max. Working Pressure (psi) at 70°F/140°F	Weight		Min. Bend Radius (in)	Clamp Size (mm)
		ID (in)	OD (in)		(lbs)	(kgs)		
500-03125X100	100' Boxed Coil	3/16	7/16	45/30	5.0	2.3	2.0	12.3
500-04125X100	100' Boxed Coil	1/4	1/2	35/25	5.9	2.7	3.0	13.3
500-05125X100	100' Boxed Coil	5/16	9/16	30/20	7.1	3.2	3.8	15.7
500-06125X100	100' Boxed Coil	3/8	5/8	25/15	7.9	3.6	4.5	17.0

Certifications:

FDA Food Contact Compliance CFR (21 CFR 177.1630)
NSF-51 Food Equipment

Because we continually examine ways to improve our products, we reserve the right to alter specifications without notice.

Accuflex Beverage Transfer Products

Cautionary Statement

All Products sold and distributed by Accuflex Industrial Hose, Ltd. are in the nature of commodities and they are sold by published specifications and not for particular purposes, uses or applications. Purchaser shall first determine their suitability for the intended purposes, uses or applications and shall either conduct its own engineering studies or tests, or retain qualified engineers, consultants or testing laboratories and consult with them before determining the proper use, suitability or propriety of the merchandise or Products for the intended purposes, uses or applications.

Accuflex Industrial Hose, Ltd. ("Seller") does not recommend the Products for any particular purpose, use or application, and the Purchaser or user thereof shall assume full responsibility for the suitability, propriety, use and application of the Products. Purchaser shall follow all instructions contained in Seller's catalogs, brochures, technical bulletins and other documents regarding the Products. The Products, including but not limited to, hose, tubing or couplings, may fail due to the use or conveyance of substances at elevated or lowered temperatures or at excessive pressure, the conveyance of abrasive, injurious, flammable, explosive or damaging substances.

Hose or tubing used in bent configurations will be subjected to increased abrasion. Hose clamps or couplings may loosen after initial installation and all sections of hose and tubing including connections, couplings, clamps, conductivity and bonding should be inspected frequently, regularly and consistently, and should be replaced, adjusted or re-tightened for the avoidance of leakage, for the prevention of injuries or damages, and for general safety purposes. Except as indicated in its Limited Warranty, Seller shall not be liable or responsible for direct or indirect injuries or damages caused by or attributed to the failure or malfunction of any Products sold or distributed by it.

Purchasers or users of the Products should frequently and consistently undertake inspections and protective measures with respect to the use and application of Products, which should include the examination of tube and cover, conditions of the hose or tubing, and the identification, repair or replacement of sections showing cracking, blistering, separations, internal and external abrasions, leaking or slipped couplings or connections and make proper proof tests.

Limited Warranty

The Products sold or distributed by Seller are warranted to its customers to be free from defects in material and workmanship at the time of shipment by us, subject to the following provisions.

ALL WARRANTY CLAIMS SHALL BE MADE WITHIN SIX (6) MONTHS AFTER SELLER SHIPPED THE PRODUCTS. SELLER'S LIABILITY HEREUNDER IS LIMITED AT SELLER'S EXCLUSIVE DISCRETION, TO 1) THE PURCHASE PRICE OF ANY PRODUCTS PROVING DEFECTIVE; 2) REPAIR OF ANY DEFECTIVE PRODUCT OR PART THEREOF; OR 3) REPLACEMENT OF ANY DEFECTIVE PRODUCT OR PART UPON ITS AUTHORIZED RETURN TO SELLER.

THIS WARRANTY IS IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE CREATED UNDER APPLICABLE LAW INCLUDING, BUT NOT LIMITED TO, THE WARRANTY OF MERCHANTABILITY AND THE WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT

SHALL SELLER OR THE MANUFACTURER OF THE PRODUCT BE LIABLE FOR SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING LOSS OF PROFITS, WHETHER OR NOT CAUSED BY OR RESULTING FROM THE NEGLIGENCE OF SELLER AND/OR THE MANUFACTURER OF THE PRODUCT, UNLESS SPECIFICALLY PROVIDED HEREIN. IN ADDITION, THIS WARRANTY SHALL NOT APPLY TO ANY PRODUCTS OR PORTIONS THEREOF WHICH HAVE BEEN SUBJECTED TO ABUSE, MISUSE, IMPROPER INSTALLATION, MAINTENANCE, OR OPERATION, ELECTRICAL FAILURE OR ABNORMAL CONDITIONS, AND TO PRODUCTS WHICH HAVE BEEN TAMPED WITH, ALTERED, MODIFIED, REPAIRED, REWORKED BY ANYONE NOT APPROVED BY SELLER, OR USED IN ANY MANNER INCONSISTENT WITH THE PROVISIONS OF THE "CAUTIONARY STATEMENT" ABOVE OR ANY INSTRUCTIONS OR SPECIFICATIONS PROVIDED WITH OR FOR THE PRODUCT.

10/2004



Accuflex Industrial Hose, Ltd. A Kuriyama Group Company

36663 Van Born Road, Suite 300
Romulus, MI 48174
Phone: (734) 713-4100
FAX: (734) 713-4190

Web Site: <https://www.accuflex.com>
E-Mail: sales@accuflex.com

Kuri Tec Corporation A Kuriyama Group Company

140 Roy Boulevard
Brantford, ON, Canada N3R 7K2
Phone: (519) 753-6717
FAX: (519) 753-7737

Web Site: <https://www.kuritec.com>
E-Mail: sales@kuritec.com

Bev-Seal® Bev-Steel®, Bevlex®, Bev-Flex®, CLEARBRAID®, and Glas-Flex™ are registered trademarks of Kuriyama of America, Inc., Schaumburg, Illinois
Bev-Seal Ultra® and Polyspring® are registered trademarks of Kuriyama of America, Inc., Schaumburg, Illinois.
Klearon™ and Sani-Clean AM™ are trademarks of Kuriyama of America, Inc., Schaumburg, Illinois.